


Filter, Series 652

- G 1/4 G 3/8 G 1/2

- filter porosity 5 25 µm



Type

Parts

Working pressure min./max.

Ambient temperature min./max.

Medium temperature min./max.

Medium

Condensate drain

Weight

Can be assembled into blocks

Filter

0 ... 16 bar

-20 ... 50 °C

-20 ... 50 °C

Extended temperature range min./max.
(optional) -40 °C ... 80 °C

Compressed air Neutral gases

See table below

See table below

The delivered product varies from that in the illustration. See the drawing for an exact description.

Technical data

Part No.	Port	filter porosity	Flow Qn	Condensate drain
G652ABBK2JA000A	G 1/4	5 µm	2250 l/min	fully automatic, open without pressure
G652ABBK2JA000N	G 1/4	5 µm	2024 l/min	semi-automatic, open without pressure
G652ABJK2JA000A	G 1/4	25 µm	2250 l/min	fully automatic, open without pressure
G652ABBK3JA000A	G 3/8	5 µm	2185 l/min	fully automatic, open without pressure
G652ABBL2JA000A	G 1/4	5 µm	2250 l/min	fully automatic, open without pressure
G652ABJK3JA000A	G 3/8	25 µm	3390 l/min	fully automatic, open without pressure
G652ABBK3JA000N	G 3/8	5 µm	2185 l/min	semi-automatic, open without pressure
G652ABBK4JA000A	G 1/2	5 µm	2290 l/min	fully automatic, open without pressure
G652ABBK4JA000N	G 1/2	5 µm	2290 l/min	semi-automatic, open without pressure
G652ABBL2JA000N	G 1/4	5 µm	2024 l/min	semi-automatic, open without pressure
G652ABBL3JA000A	G 3/8	5 µm	2190 l/min	fully automatic, open without pressure
G652ABBL3JA000N	G 3/8	5 µm	2185 l/min	semi-automatic, open without pressure
G652ABBL4JA000A	G 1/2	5 µm	2290 l/min	fully automatic, open without pressure
G652ABBL4JA000N	G 1/2	5 µm	2290 l/min	semi-automatic, open without pressure
G652ABBP2JA000A	G 1/4	5 µm	2024 l/min	fully automatic, open without pressure
G652ABBP2JA000N	G 1/4	5 µm	2024 l/min	semi-automatic, open without pressure
G652ABBP3JA000A	G 3/8	5 µm	2185 l/min	fully automatic, open without pressure
G652ABBP3JA000N	G 3/8	5 µm	2185 l/min	semi-automatic, open without pressure
G652ABBP4JA000A	G 1/2	5 µm	2290 l/min	fully automatic, open without pressure
G652ABBP4JA000N	G 1/2	5 µm	2290 l/min	semi-automatic, open without pressure
G652ABJK2JA000N	G 1/4	25 µm	2550 l/min	semi-automatic, open without pressure
G652ABJK3JA000N	G 3/8	25 µm	3390 l/min	semi-automatic, open without pressure
G652ABJK4JA000A	G 1/2	25 µm	3620 l/min	fully automatic, open without pressure

Part No.	Port	filter porosity	Flow Qn	Condensate drain
G652ABJK4JA000N	G 1/2	25 µm	3700 l/min	semi-automatic, open without pressure
G652ABJL2JA000A	G 1/4	25 µm	2550 l/min	fully automatic, open without pressure
G652ABJL2JA000N	G 1/4	25 µm	2550 l/min	semi-automatic, open without pressure
G652ABJL3JA000A	G 3/8	25 µm	3390 l/min	fully automatic, open without pressure
G652ABJL3JA000N	G 3/8	25 µm	3390 l/min	semi-automatic, open without pressure
G652ABJL4JA000A	G 1/2	25 µm	3700 l/min	fully automatic, open without pressure
G652ABJL4JA000N	G 1/2	25 µm	3620 l/min	semi-automatic, open without pressure
G652ABJP2JA000A	G 1/4	25 µm	2250 l/min	fully automatic, open without pressure
G652ABJP2JA000N	G 1/4	25 µm	2250 l/min	semi-automatic, open without pressure
G652ABJP3JA000A	G 3/8	25 µm	3390 l/min	fully automatic, open without pressure
G652ABJP3JA000N	G 3/8	25 µm	3390 l/min	semi-automatic, open without pressure
G652ABJP4JA000A	G 1/2	25 µm	3620 l/min	fully automatic, open without pressure
G652ABJP4JA000N	G 1/2	25 µm	3620 l/min	semi-automatic, open without pressure

Part No.	Material Condensate drain	Version
G652ABBK2JA000A	Brass	Metal reservoir without window
G652ABBK2JA000N	Plastic	Metal reservoir without window
G652ABJK2JA000A	Brass	Metal reservoir without window
G652ABBK3JA000A	Brass	Metal reservoir without window
G652ABBL2JA000A	Brass	reservoir, metal, with inspection glass
G652ABJK3JA000A	Brass	Metal reservoir without window
G652ABBK3JA000N	Plastic	Metal reservoir without window
G652ABBK4JA000A	Brass	Metal reservoir without window
G652ABBK4JA000N	Plastic	Metal reservoir without window
G652ABBL2JA000N	Plastic	reservoir, metal, with inspection glass
G652ABBL3JA000A	Brass	reservoir, metal, with inspection glass
G652ABBL3JA000N	Plastic	reservoir, metal, with inspection glass
G652ABBL4JA000A	Brass	reservoir, metal, with inspection glass
G652ABBL4JA000N	Plastic	reservoir, metal, with inspection glass
G652ABBP2JA000A	Brass	reservoir, polycarbonate, with PA protective guard
G652ABBP2JA000N	Plastic	reservoir, polycarbonate, with PA protective guard
G652ABBP3JA000A	Brass	reservoir, polycarbonate, with PA protective guard
G652ABBP3JA000N	Plastic	reservoir, polycarbonate, with PA protective guard
G652ABBP4JA000A	Brass	reservoir, polycarbonate, with PA protective guard
G652ABBP4JA000N	Plastic	reservoir, polycarbonate, with PA protective guard
G652ABJK2JA000N	Plastic	Metal reservoir without window
G652ABJK3JA000N	Plastic	Metal reservoir without window
G652ABJK4JA000A	Brass	Metal reservoir without window
G652ABJK4JA000N	Plastic	Metal reservoir without window
G652ABJL2JA000A	Brass	reservoir, metal, with inspection glass
G652ABJL2JA000N	Plastic	reservoir, metal, with inspection glass
G652ABJL3JA000A	Brass	reservoir, metal, with inspection glass
G652ABJL3JA000N	Plastic	reservoir, metal, with inspection glass
G652ABJL4JA000A	Brass	reservoir, metal, with inspection glass
G652ABJL4JA000N	Plastic	reservoir, metal, with inspection glass
G652ABJP2JA000A	Brass	reservoir, polycarbonate, with PA protective guard
G652ABJP2JA000N	Plastic	reservoir, polycarbonate, with PA protective guard

Part No.	Material Condensate drain	Version
G652ABJP3JA000A	Brass	reservoir, polycarbonate, with PA protective guard
G652ABJP3JA000N	Plastic	reservoir, polycarbonate, with PA protective guard
G652ABJP4JA000A	Brass	reservoir, polycarbonate, with PA protective guard
G652ABJP4JA000N	Plastic	reservoir, polycarbonate, with PA protective guard

Part No.	Weight
G652ABBK2JA000A	0,55 kg
G652ABBK2JA000N	0,55 kg
G652ABJK2JA000A	0,55 kg
G652ABBK3JA000A	0,55 kg
G652ABBL2JA000A	0,55 kg
G652ABJK3JA000A	0,55 kg
G652ABBK3JA000N	0,55 kg
G652ABBK4JA000A	0,55 kg
G652ABBK4JA000N	0,55 kg
G652ABBL2JA000N	0,55 kg
G652ABBL3JA000A	0,57 kg
G652ABBL3JA000N	0,55 kg
G652ABBL4JA000A	0,55 kg
G652ABBL4JA000N	0,55 kg
G652ABBP2JA000A	0,43 kg
G652ABBP2JA000N	0,43 kg
G652ABBP3JA000A	0,43 kg
G652ABBP3JA000N	0,43 kg
G652ABBP4JA000A	0,43 kg
G652ABBP4JA000N	0,43 kg
G652ABJK2JA000N	0,55 kg
G652ABJK3JA000N	0,55 kg
G652ABJK4JA000A	0,55 kg
G652ABJK4JA000N	0,55 kg
G652ABJL2JA000A	0,55 kg
G652ABJL2JA000N	0,55 kg
G652ABJL3JA000A	0,55 kg
G652ABJL3JA000N	0,55 kg
G652ABJL4JA000A	0,55 kg
G652ABJL4JA000N	0,55 kg
G652ABJP2JA000A	0,43 kg
G652ABJP2JA000N	0,43 kg
G652ABJP3JA000A	0,43 kg
G652ABJP3JA000N	0,43 kg
G652ABJP4JA000A	0,43 kg
G652ABJP4JA000N	0,43 kg

Nominal flow Q_n at p₁= 10 bar , p₂= 6.3 bar and Δp = 1 bar

Technical information


Max. achievable compressed air class acc. to ISO 8573-1:2010 5 : 8 : 4 (5 µm filter porosity) und 6 : 8 : 4 (25µm filter porosity)
 Other filter porosities on request.

Technical information

Material	
Housing	Aluminum
Seals	Nitrile butadiene rubber
Filter insert	Sintered polyethylene
Condensate drain	Brass Plastic

Dimensions

Dimensions




*Variable dimension based on the type of drain specified, if an automatic drain is specified, add another 5 mm to the “G” dimension, which also adds 5 mm to the “A” dimension.

Dimensions


Series	A	B	C	D	E	F	G	H	J	K	L	M	N	P	Q	R	S	T
652	217	38,3	66	33	69	34,5	25	50	1,9	53	106	11	10	20	6,3	11	42	84

Diagrams


Flow diagram, G 1/4



Flow diagram, G 3/8




Flow diagram, G 1/2



Accessories overview

Accessories overview



Ordering information

Thread connection
 G = ISO 228/1-G ⁽¹⁾
 8 = NPTF

Product series
 651
 652
 653

Revision letter
 A

Product type
 B = Filter - Particulate

Elements
 B = 5 µm (White)
 J = 25 µm (Yellow)

Bowl type
 K = Metal bowl without sight gauge
 L = Metal bowl with sight gauge (glass)
 P = Polycarbonate bowl with bowl guard

Drain type
 0 = Without
 A = Auto drain normally open
 N = Manual/Semi-automatic drain
 Q = Manual drain - Stainless steel

Options ⁽²⁾
 A00 = Without option
 101 = Side Mounting Brackets
 105 = High temperature (+80°C)
 106 = Low temperature (-40°C) ⁽³⁾
 109 = FPM seals
 117 = ATEX zones 1-21 
 124 = CUTR Certification (EAC)
 125 = CUTR Ex
 202 = 105 + 109
 2A9 = 105 + 106

Port size
 1 = 1/8 (651 Series)
 2 = 1/4 (651 or 652 Series)
 3 = 3/8 (652 Series)
 4 = 1/2 (652 Series)
 5 = 3/4 (653 Series)
 6 = 1 (653 Series)

Images:
 - Thread connection: G (ISO 228/1-G) and 8 (NPTF)
 - Product series: 651, 652, 653
 - Revision letter: A
 - Product type: B (Filter - Particulate)
 - Elements: B (5 µm White) and J (25 µm Yellow)
 - Bowl type: K (Metal bowl without sight gauge), L (Metal bowl with sight gauge), P (Polycarbonate bowl with bowl guard)
 - Drain type: A (Auto drain normally open), N (Manual/Semi-automatic drain), Q (Manual drain - Stainless steel)
 - Options: 101 (Side Mounting Brackets)
 - Port size: 1 (1/8), 2 (1/4), 3 (3/8), 4 (1/2), 5 (3/4), 6 (1)

Efficient pneumatic solutions, our program: cylinders and drives, valves and valve systems, air supply management



Visit us: [Emerson.com/Aventics](https://www.emerson.com/Aventics)

Your local contact: [Emerson.com/contactus](https://www.emerson.com/contactus)



Emerson.com



Facebook.com/EmersonAutomationSolutions



LinkedIn.com/company/Emerson-Automation-Solutions



Twitter.com/EMR_Automation

An example configuration is depicted on the title page. The delivered product may thus vary from that in the illustration. Subject to change. This Document, as well as the data, specifications and other information set forth in it, are the exclusive property of AVENTICS GmbH. It may not be reproduced or given to third parties without its consent. Only use the AVENTICS products shown in industrial applications. Read the product documentation completely and carefully before using the product. Observe the applicable regulations and laws of the respective country. When integrating the product into applications, note the system manufacturer's specifications for safe use of the product. The data specified only serve to describe the product. No statements concerning a certain condition or suitability for a certain application can be derived from our information. The information given does not release the user from the obligation of own judgement and verification. It must be remembered that the products are subject to a natural process of wear and aging.

The Emerson logo is a trademark and service mark of Emerson Electric Co. Brand logotype are registered trademarks of one of the Emerson family of companies. All other marks are the property of their respective owners. © 2020 Emerson Electric Co. All rights reserved.
2020-12



CONSIDER IT SOLVED™